

LubriEdge Rust Oil WDM (Rust preventive oil based) - Product Data Sheet

Product: LubriEdge Rust Oil WDM are non solvent type oily film forming type rust preventive oils with different viscosities and film thickness.LubriEdge Rust Oil blended from selected base stocks and special additives to ensure excellent protection of metal components against rusting for longer and shorter duration in indoor and outdoor applications respectively.Because of its non-drying characteristics,the removal of LubriEdge Rust oil WDM from the metal components is easier by treating with petroleum solvents,alkaline cleaning or vapour degreasing agents and do not require any special precautions during storage,handling and applications as they are free from any solvent.

Specifications : Proprietary Grade

Benefits :

- Excellent protection against rust and corrosion.
- Dries to form a non-stick & dry feel film after 60-90 minutes application
- Protective film that does not get scratched easily and protects during handling and outdoor storage

Typical Properties :

Characteristics	Test Methods	Unit	WDM 105	WDM 115	WDM 125
Kinematic Viscosity at 40°C	ASTM D 445	cSt	15	24	450
Film thickness,min	IS 2074	micron	2	2	25
Flash Point , COC min	ASTM D 92	°C	130	160	230
Copper strip corrosion Test@100 for 3 hrs	ASTM D130	-	1	1	1

Note : Above mentioned properties are typical values of the product range and doesn't represent specification of the product. Regarding these products, OFB Tech Private Ltd provides no express or implied warranties, representations, or conditions of any kind. It is entirely the users' obligation to determine if the product is suitable in the end for the intended usage.

Storage : Every package needs to be kept covered in storage. Steer clear of heat or the sun. To prevent contamination, keep the container well closed and sealed.

Safety : Please dispose of this product carefully to prevent contaminating the environment, as you would with any product. Don't pour spent oil down the drain or into the water. Steer clear of the eyes and skin. Cleanse with soap and water after skin contact. When used as directed and the safety data sheet (SDS) instructions are followed, this product shouldn't have any negative health effects.

OFB Tech Private Limited

CORPORATE OFFICE : 6th Floor, Tower-A, Global Business Park, M.G. Road, Gurugram, Haryana-122001

DUBAI OFFICE : Office No. E2-120G-23, Hamriyah Free Zone, Sharjah, United Arab Emirates.

